

1. Nominal Capacity : Discharged at room temperature(20℃) and cut-offed at 2.0V
2. BB : Bobbin Constructions, GMS : Glass To Metal Seal, HW : Hermetic Weld (Sealing Method)
3. Model : F Series – Lithium Foil, P Series – Lithium Power (Under Development)

Product Cross Reference						
Cell Size	XenoEnergy	Tadiran	Saft	Sonnenschein	Toshiba	Maxel
1/2AA	XL-050F (1.2)	TL-2150 (0.95) TL-4902 (1.2) TL-5101 (0.95) TL-5151 (0.7) TL-5902 (1.2)	LS-14250 (1.0) LS-14250C (1.2)	SL-350 (1.0) SL-750 (0.95)	ER3V (1.0) ER4V (1.2)	ER3 (0.9) ER3S (0.9)
AA	XL-060F (2.4)	TL-2100 (2.1) TL-4903 (2.4) TL-5104 (2.1) TL-5903 (2.4)	LS14500 (2.25) LS14500C (2.75)	SL-360 (2.3) SL-760 (2.1)	ER6V (2.0) ER6LV (1.8)	ER6 (2.0) ER6C (1.8)
C	XL-140F (7.2) XL-145F (8.5)	TL-2200 (7.2) TL-4920 (8.5) TL-5920 (8.5)	LS26500 (7.2) LS26500C (8.5)	SL-770 (7.2)		
D	XL-200F (16.5) XL-205F (19.0)	TL-2300 (16.5) TL-4930 (19) TL-5930 (19)	LS33600 (16.5) LS33600C (18.5)	SL-780 (16.5)		

Copyright 2003 XenoEnergy Co. Ltd., All Rights Reserved

